

**Standards**

ISO 20345 SB HRO SRC  
E FO  
RTE SERECT ST HTA  
70A ind E § 3.4 MAX 1  
000 V AC

**MV-226-..**

Safety shoes with insulating sole, textile and low type

**Application:**

- Safety shoes, low, textile model, with 1000 V AC insulating sole according to RTE SERECT ST HTA 70A ind E § 3.4.
- Ventilated shoes for comfortable use in hot environments, indoors or on dry ground.
- Shoes with insulated soles specially designed for electricians, industry, logistics and transport, crafts.



**Features:**

- Shoes with “3D mesh ventilated quarters” upper.
- Sole: PU/nitrile rubber.
- Front and rear leather reinforcements.
- Breathable, absorbent anti-bacterial lining.
- Metal-free protective toe cap.
- SB: basic protection.
- HRO: direct contact heat resistance.
- SRC (SRA + SRB) : Adhesion, slip resistance on ceramic tiles and steel floor.
- E: Heel energy absorption capacity.
- FO: Resistance to hydrocarbons.
- Unit test of each shoe before dispatch in accordance with RTE SERECT specification No. ST HTA ind E to validate resistance to test voltage: 5 kV/1 min.

Reference	Size	Voltage		Weight (kg)
		Operating Voltage	AC	
MV-226-40	40	1 000 V		1,29
MV-226-41	41	1 000 V		1,34
MV-226-42	42	1 000 V		1,39
MV-226-43	43	1 000 V		1,5
MV-226-44	44	1 000 V		1,9
MV-226-45	45	1 000 V		1,56
MV-226-46	46	1 000 V		1,5
MV-226-47	47	1 000 V		1,62