

CGM-3-...-410

Network Type : MV

Insulating gloves with mechanical protection and Arc Flash
 12 cal/cm², class 3 - 26 500 V AC, length : 410 mm

Application:

- Wellfit finish: soft, supple, durable and ergonomic with high flexibility to ease the work.
- Convenient to any hand shape.
- Resistant: latex with reinforced mechanical protection against tearing. To be used without over-gloves.
- Protection against the thermal hazards of an electric arc 12 cal/cm². IEC 61482-1-2 APC 2 (box test 7 kA).



Features:

- Electrical insulating gloves, class 3 (26 500 V AC, 39 750 V DC).
- Cut edges.
- Material: bicolor natural latex. (exterior: orange, interior: natural).
- Traceability through flashcode on color-coded label. The color is according to the class.
- Category: RC (Acid, Ozone, Cold, Oil resistance).



| Reference | Size | Length (mm) | Class | Voltage | | ATPV (cal/cm ²) | Arc | |
|--------------|------|-------------|-------|----------------------|----------------------|-----------------------------|-------------|----------|
| | | | | Operating Voltage AC | Operating Voltage DC | | Box Test | Category |
| CGM-3-10-410 | 10 | 410 | 3 | 26 500 V | 39 750 V | 12 | 7kA / 30 cm | RC |