

CGM-2-...-410

Network Type : MV

Insulating gloves with mechanical protection and Arc Flash,
length : 410 mm

Application:

- Wellfit finish: soft, supple, durable and ergonomic with high flexibility to ease the work.
- Convenient to any hand shape.
- Resistant: latex with reinforced mechanical protection against tearing. To be used without over-gloves.
- Protection against the thermal hazards of an electric arc 12 cal/cm². IEC 61482-1-2 APC 2 (box test 7 kA).

Features:

- Electrical insulating gloves, class 2 (17 000 V AC, 25 500 V DC).
- Cut edges.
- Material: bicolor natural latex. (exterior: orange, interior: natural).
- Traceability through flashcode on color-coded label. The color is according to the class.
- Category: RC (Acid, Ozone, Cold, Oil resistance).



Reference	Size	Length (mm)	Class	Voltage		ATPV (cal/cm ²)	Arc Box Test	Category
				Operating Voltage AC	Operating Voltage DC			
CGM-2-08-410	8	410	2	17 000 V	25 500 V	12	7kA / 30 cm	RC
CGM-2-09-410	9	410	2	17 000 V	25 500 V	12	7kA / 30 cm	RC
CGM-2-10-410	10	410	2	17 000 V	25 500 V	12	7kA / 30 cm	RC
CGM-2-11-410	11	410	2	17 000 V	25 500 V	12	7kA / 30 cm	RC
CGM-2-12-410	12	410	2	17 000 V	25 500 V	12	7kA / 30 cm	RC