

PP-4-38-...

Insulating safety padlock with retaining key, nylon shackle H 38 mm Ø 4 mm

Application :

- For locking the separating devices (e.g. circuit breakers) to prevent their operation.
- Padlock with insulating shackle for use in low voltage 1000 V AC - 1500 V DC: tested and validated in accordance with the electrical test IEC 60900 (2012) §5.5.3. at 5 000 V.
- More secure locking: impossible to drop the key when the shackle is open, the key remains trapped.

Features :

- Available with a keys alike (A1 to A6) or different (Z).
- Marking on both sides:
 1. On one side: Standard symbol.
 2. On the other side: area for marking user names and coordinates.
- Padlock delivered with 2 keys.



| Ref. | Description | | Diameter | Characteristics |
|--------------|-------------|------------|----------|-----------------|
| | Color | Key Number | Shackle | Weight |
| PP-4-38-B-A1 | ■ | A1 | 4 | 90g |
| PP-4-38-B-A2 | ■ | A2 | 4 | 90g |
| PP-4-38-B-A3 | ■ | A3 | 4 | 90g |
| PP-4-38-B-A4 | ■ | A4 | 4 | 90g |
| PP-4-38-B-A5 | ■ | A5 | 4 | 90g |
| PP-4-38-B-A6 | ■ | A6 | 4 | 90g |
| PP-4-38-B-Z | ■ | Z | 4 | 90g |