

**CG-984-..**

Network Type : LV

Short leather overgloves for low voltage insulating gloves with Arc Flash protection 12 cal/cm<sup>2</sup>

**Application:**

- Short overgloves (25 cm) ensure mechanical protection for insulating gloves for class 00 & 0, **CG-00-XX-R28**, **CG-0-XX-R28**, **CG-05** and **CG-10**.
- They Add protection against arc flash hazards up to 12 cal/cm<sup>2</sup> ATPV (according to ASTM F 2675)
- They are resistant to flame and contact heat of 100 ° C for 10 s according to EN 407.
- Velcro at the cuff adjusts the tightness of the glove to the user's hand.



**Features:**

- Silicone goat grain leather, Kevlar® thread stitching.
- Wide protective cuff in cowhide crust (10 cm long).
- American assembly, nested thumb.
- Adjustable width by fireproof Velcro strap mounted on leather.
- Grey color.
- Arc Flash Protection: ASTM F 2675 - ATPV 12 cal/cm<sup>2</sup>.
- Complies with standard EN 388: 2016 2122X
- Complies with standard EN 407: 2004 412X4X
- Level of dexterity according to EN 420 A1 : 5 (excellent grip)

**Packaging:**

- Packaging: 1 pair in a plastic bag with an instruction for use.



Reference	Size	Length (mm)	Weight (kg)	Arc ATPV (cal/cm <sup>2</sup> )
CG-984-07	7	250	0,2	12
CG-984-08	8	250	0,2	12
CG-984-09	9	250	0,2	12
CG-984-10	10	250	0,2	12
CG-984-11	11	250	0,2	12
CG-984-12	12	250	0,2	12