

Standards

ISO 20345 SB HRO SRC
E FO
RTE SERECT ST HTA
70A ind E § 3.4 MAX 1
000 V AC

MV-226-..

Safety shoes with insulating sole, textile and low type

Application:

- Safety shoes, low, textile model, with 1000 V AC insulating sole according to RTE SERECT ST HTA 70A ind E § 3.4.
- Ventilated shoes for comfortable use in hot environments, indoors or on dry ground.
- Shoes with insulated soles specially designed for electricians, industry, logistics and transport, crafts.



Features:

- Shoes with “3D mesh ventilated quarters” upper.
- Sole: PU/nitrile rubber.
- Front and rear leather reinforcements.
- Breathable, absorbent anti-bacterial lining.
- Metal-free protective toe cap.
- SB: basic protection.
- HRO: direct contact heat resistance.
- SRC (SRA + SRB) : Adhesion, slip resistance on ceramic tiles and steel floor.
- E: Heel energy absorption capacity.
- FO: Resistance to hydrocarbons.
- Unit test of each shoe before dispatch in accordance with RTE SERECT specification No. ST HTA ind E to validate resistance to test voltage: 5 kV/1 min.

Reference	Size	Voltage	Weight (kg)
		Operating Voltage AC	
MV-226-42	42	1 000 V	1,39