



**Standards** ISO 20345 SB HRO SRC E FO RTE SERECT ST HTA 70A ind E § 3.4 MAX 1 000 V AC



## Safety shoes with insulating sole, textile and high type

## **Application:**

- · Safety shoes, high, textile model, with 1000 V AC insulating sole according to RTE SERECT ST HTA 70A ind E § 3.4.
- Ventilated shoes for comfortable use in hot environments, indoors or on dry ground.
- Shoes with insulated soles specially designed for electricians, industry, • logistics and transport, crafts.



## Features:

- Shoes with "3D mesh ventilated quarters" upper.
- Sole: PU/nitrile rubber. •
- · Front and rear leather reinforcements.
- Breathable, absorbent anti-bacterial lining.
- Metal-free protective toe cap.
- SB: basic protection. •
- HRO: direct contact heat resistance. ٠
- SRC (SRA + SRB) : Adhesion, slip resistance on ceramic tiles and steel • floor.
- E: Heel energy absorption capacity. ٠
- FO: Resistance to hydrocarbons.
- Unit test of each shoe before dispatch in accordance with RTE SERECT • specification No. ST HTA ind E to validate resistance to test voltage: 5 kV/1 min.

		Voltage	
Reference	Size	Operating Voltage AC	Weight (kg)
MV-227-44	44	1 000 V	1.50



France

www.catuelec.com

UID : | TID : :: 01/01/1970| SID : :: 01/01/1970 | Issued :04/27/2025 11:22:00 pm

