

MO-68...

Insulated T-Bar Box Spanner

Application:

- Insulated T-Bar Box Spanner for live working at low voltage with circuits that can't be disconnected.
- The CATU T-Bar Box Spanner is safely insulated against voltages of up to 1000 V AC - 1500 V conforming to IEC 60900:2018 standards.
- Orange hardened PVC insulated grips allow for comfort and reduces the strain placed on your hand.

Features:

- Maximum operating voltage: 1 000 V AC - 1 500 V DC.
- Orange hardened PVC insulation.
- Treated hex steel tube
- 6 or 12 sided socket variants.



Ref	Length (mm)	Weight (kg)	Voltages for use		Profile
			Operating Voltage AC	Operating Voltage DC	
MO-68610	145	0.150	1 000 V	1 500 V	10 mm
MO-68613	145	0.200	1 000 V	1 500 V	13 mm
MO-68614	145	0.200	1 000 V	1 500 V	14 mm
MO-68620	145	0.350	1 000 V	1 500 V	20 mm
MO-68621	145	0.370	1 000 V	1 500 V	21 mm
MO-68310	305	0.330	1 000 V	1 500 V	10 mm
MO-68311	305	0.490	1 000 V	1 500 V	11 mm
MO-68312	305	0.530	1 000 V	1 500 V	12 mm
MO-68313	305	0.590	1 000 V	1 500 V	13 mm
MO-68314	305	0.590	1 000 V	1 500 V	14 mm
MO-68316	305	0.640	1 000 V	1 500 V	16 mm
MO-68317	305	0.660	1 000 V	1 500 V	17 mm
MO-68319	305	0.750	1 000 V	1 500 V	19 mm
MO-68321	305	0.840	1 000 V	1 500 V	21 mm
MO-68322	305	0.890	1 000 V	1 500 V	22 mm
MO-68713	405	0.650	1 000 V	1 500 V	13 mm
MO-68714	405	0.800	1 000 V	1 500 V	14 mm
MO-68717	405	0.900	1 000 V	1 500 V	17 mm