

## CC-765-...

Network Type : MV

### Electronic voltage detector (Medium Voltage)

#### Application:

- Electronic voltage detector for indoor and outdoor use, with high level of shock, vibration and rain resistance.
- Capacitive head technology, ultra compact.
- Broad voltage range, operating frequency 50 and 60 Hz.

#### Features:

- Robust thermoplastic housing.
- Voltage presence signaled by:
  - Flashing red LEDs;
  - Powerful audible signal (67 dB (A)/1.5 m);
  - Visible over 360° with lighting and display.
- Contact electrodes easily interchangeable.

#### Composition:

- Supplied with an end-fitting matching the insulating stick terminal:
  - C: hexagonal 12 mm for sticks with C fitting;
  - K: universal for sticks with K fitting;
  - U: UDI end-fitting with a U shape (55 mm overhang) for sticks with UDI end-fitting.
- Supplied in a carrying case.

#### Optional accessories:

- Recommended insulating sticks: [CE-4-21](#) series.



Référence	Description		Voltage range	Frequency	Weight (kg)
		Fitting			
CC-765-2/72-C		C	2 - 7,2 kV	50 / 60 Hz	0,600
CC-765-2/72-K		K	2 - 7,2 kV	50 / 60 Hz	0,600
CC-765-3/10-C		C	3 - 10 kV	50 / 60 Hz	0,600
CC-765-3/10-K		K	3 - 10 kV	50 / 60 Hz	0,600
CC-765-3/10-U		UDI	3 - 10 kV	50 / 60 Hz	0,600
CC-765-55/20-C		C	5,5 - 20 kV	50 / 60 Hz	0,600
CC-765-55/20-K		K	5,5 - 20 kV	50 / 60 Hz	0,600
CC-765-55/20-U		UDI	5,5 - 20 kV	50 / 60 Hz	0,600
CC-765-10/30-C		C	10 - 30 kV	50 / 60 Hz	0,600
CC-765-10/30-K		K	10 - 30 kV	50 / 60 Hz	0,600
CC-765-10/30-U		UDI	10 - 30 kV	50 / 60 Hz	0,600
CC-765-10/36-C		C	10 - 36 kV	50 / 60 Hz	0,600
CC-765-10/36-K		K	10 - 36 kV	50 / 60 Hz	0,600

Référence	Description		Voltage range	Frequency	Weight (kg)
	Fitting				
CC-765-10/36-U	UDI		10 - 36 kV	50 / 60 Hz	0,600
CC-765-15/45-C	C		15 - 45 kV	50 / 60 Hz	0,600
CC-765-15/45-K	K		15 - 45 kV	50 / 60 Hz	0,600
CC-765-30/66-K	K		30 - 66 kV	50 / 60 Hz	0,600
CC-765-25-C	C		25 kV	50 / 60 Hz	0,450
CC-765-03-10-M-3	-		3 - 10 kV	50 / 60 Hz	0,600