

CC-260-...

Voltage detector, high voltage (HV)

Application :

- Electronic voltage detector for outdoor use with high resistance to shock, vibration and rain.
- Capacitive head technology, ultra compact.
- Operating voltage: 60 to 550 kV.

Features :

- Housing / electronic circuit design with quick release for easy battery replacement.
- Double signalisation with presence of voltage indicated at the same time by :
 - Bright red flashing light-emitting diodes (visible at more than 50 meters even in direct lighting),
 - Strong nominal acoustic signal (67 dB (A)/1,5 m).
 - 360° vision with illuminated display for optimum visibility.
- Interchangeable contact electrodes.

Composition :

- Supplied with 3 tips to fit on the poles:
 - W: hexagonal 20 mm on flat,
 - C: hexagonal 12 mm on flat,
 - K: universal.
- Supplied with a shock-proof case with handle.

Optional accessories :

- Hook type contact electrode diam. 60 mm. Reference: CC-ANT60
- Hook type contact electrode diam. 120 mm. Reference: CC-ANT120
- Hook type contact electrode diam. 200 mm. Reference: CC-ANT200
- Recommended insulating sticks: [CM-46](#), [CE-430](#), [CE-9](#)



Référence	Voltage range	Frequency	Weight (kg)
CC-260-60/235	60 - 235 kV	50 / 60 Hz	1,2
CC-260-132/380	132 - 380 kV	50 / 60 Hz	1,2
CC-260-150/420	150 - 420 kV	50 / 60 Hz	1,2
CC-260-225/550	225 - 550 kV	50 / 60 Hz	1,2