





Standards EN 60903:2003 IEC 60903:2014 IEC 61482-2 ASTM F2675

Network Type: MV

CGM-3..

Insulating gloves with mechanical protection and Arc Flash 12 cal/cm², class 3 - 26 500 V AC, length: 360 mm

Application:

- · Wellfit finish: soft, supple, durable and ergonomic with high flexibility to ease the work.
- Convenient to any hand shape.
- · Resistant: latex with reinforced mechanical protection against tearing. To be used without over-gloves.
- Protection against the thermal hazards of an electric arc 12 cal/cm². IEC 61482-1-2 APC 2 (box test 7 kA).



- Electrical insulating gloves, class 3 (26 500 V AC, 39 750 V DC).
- Material: bicolor natural latex. (exterior: orange, interior: natural).
- Traceability through flashcode on color-coded label. The color is according to the class.
- · Category: RC (Acid, Ozone, Cold, Oil resistance).





	Reference	Size	Length (mm)	Class	Voltage			Arc	
					Operating Voltage AC	Operating Voltage DC	ATPV (cal/cm²)	Box Test	Category
	CGM-3-10	10	360	3	26 500 V	39 750 V	12	7kA / 30 cm	RC



UID: | TID: :: 01/01/1970 | SID: :: 01/01/1970 | Issued: 05/06/2025: 06:45:21 pm

Last Modification: 12/26/2024 SICAME GROUP