

**CM-44...-**

Insulated stick IEC 61235, Ø 39 mm (terminal elements)

**Application:**

- Terminal element to be combined with the elements of the CM44 series (Base and Intermediate).
- Connectable by an insulated self-locking system made of aluminium alloy.

**Features:**

- End-fittings: B, C, D, E, H, K or T. To be specified at the end of the reference.



Ref.	Length (mm)	Fitting	Weight (kg)
CM-4410-B	1200	U3 male	0,9
CM-4415-B	1160	U3 male	1,3
CM-4420-B	2200	U3 male	2,1
CM-4425-B	2700	U3 male	2,6
CM-4410-C	1140	C	0,9
CM-4415-C	1700	C	1,3
CM-4420-C	2140	C	2,1
CM-4425-C	2640	C	2,6
CM-4410-D	1210	D	0,9
CM-4415-D	1640	D	1,3
CM-4420-D	2210	D	2,1
CM-4425-D	2710	D	2,6
CM-4410-E	1110	E	0,9
CM-4415-E	1710	E	1,3
CM-4420-E	2110	E	2,1
CM-4425-E	2615	E	2,6
CM-4410-H	1130	H	0,9
CM-4415-H	1610	H	1,3
CM-4420-H	2130	H	2,1
CM-4425-H	2630	H	2,6
CM-4410-K	1130	K	0,9
CM-4415-K	1630	K	1,3
CM-4420-K	2130	K	2,1
CM-4425-K	2630	K	2,6
CM-4410-T	1130	T	0,9
CM-4415-T	1660	T	1,3
CM-4420-T	2160	T	2,1
CM-4425-T	2660	T	2,6