

MO-6600.

Insulated Combination Pliers

Application:

- Insulated combination pliers for live working at low voltage.

Features:

- Insulated to protect up to a maximum operating voltage: 1 000 V AC - 1 500 V DC.
- Orange hardened PVC insulation.
- Serrated Jaw
- Available in various lengths to suit your needs
- Special tool steel body.



Ref	Length (mm)	Weight (kg)	Voltages for use		Use
			Operating Voltage AC	Operating Voltage DC	
MO-66001	160	0.210	1 000 V	1 500 V	Cutting capacity: Copper 45 daN/mm ² : diameter 2.5 mm. Steel 80 daN/mm ² : diameter 1.6 mm. Steel 140 daN/mm ² : diameter 1 mm. Steel 200 daN/mm ² : diameter 1 mm.
MO-66002	180	0.260	1 000 V	1 500 V	Cutting capacity: Copper 45 daN/mm ² : diameter 3 mm. Steel 80 daN/mm ² : diameter 1.6 mm. Steel 140 daN/mm ² : diameter 1 mm. Steel 200 daN/mm ² : diameter 1 mm.
MO-66003	200	0.360	1 000 V	1 500 V	Cutting capacity: Copper 45 daN/mm ² : diameter 3 mm. Steel 80 daN/mm ² : diameter 1.6 mm. Steel 140 daN/mm ² : diameter 1 mm. Steel 200 daN/mm ² : diameter 1 mm.
MO-66005	250	0.560	1 000 V	1 500 V	Cutting capacity: Copper 45 daN/mm ² : diameter 5 mm. Steel 80 daN/mm ² : diameter 3 mm. Steel 140 daN/mm ² : diameter 2.5 mm. Steel 200 daN/mm ² : diameter 3 mm.