

## MP-635/..-D

Network Type : LV

### Insulated cable push-on shroud

#### Application:

Push-on shrouds offer insulation for exposed cable ends. By covering termination points, they help prevent electrical contact, minimize the risk of short circuits, and shield against damage.

- To cover the stripped ends of LV cables.
- Protects live LV connectors.
- For all installations. (Indoor, overhead and underground).
- For use on electric and hybrid vehicles and machinery.
- Maximum operating voltage: 1,000 V AC - 1,500 V DC..



#### Features:

- Cross-shaped slotted ends for inserting and holding a cable, protruding part or connector.
- Complies with NF C18-425.
- Tested at 10kV in accordance with IEC 60900:2018
- Material: semi-rigid PVC.
- Standard packaging quantity (SPQ): 5 caps.

Ref	Length (mm)	Voltages for use		Use
		Operating Voltage AC	Operating Voltage DC	
MP-635/10-D	75	1 000 V	1 500 V	For cables with external diameter of 5 to 9 mm or cross-section of 6 to 25 mm².
MP-635/15-D	100	1 000 V	1 500 V	For cables with external diameter of 7 to 13 mm or cross-section of 10 to 50 mm².
MP-635/20-D	100	1 000 V	1 500 V	For cables with external diameter of 9 to 16 mm or cross-section of 25 to 95 mm².
MP-635/25-D	100	1 000 V	1 500 V	For cables with external diameter of 12 to 20 mm or cross-section of 50 to 150 mm².
MP-635/30-D	120	1 000 V	1 500 V	For cables with external diameter of 14 to 25 mm or cross-section of 70 to 240 mm².
MP-635/40-D	135	1 000 V	1 500 V	For cables with external diameter of 16 to 30 mm or cross-section of 30 to 300 mm².
MP-635/50-D	155	1 000 V	1 500 V	For cables with external diameter of 20 to 40 mm or cross-section of 150 to 600 mm².
MP-635/60-D	180	1 000 V	1 500 V	For cables with external diameter of 25 to 50 mm or cross-section of 240 to 1000 mm².