

**Standards**

IEC 61482-2 APC 1 &  
 ATPV 12 cal/cm<sup>2</sup> ISO  
 11612 A B1 C1 F1 ISO  
 11611 class 1 EN 1149-5  
 NFPA 70E - ASTM F1959

**AFG-1001-...**

CAT'ARC multi-risk coverall to protect against electric arc  
 APC1 ATPV 12 cal/cm<sup>2</sup>

**Application:**

- Multi-risk protection: protection against thermal hazards of an electric arc, heat and flames, welding hazards and antistatic.
- Prevention of the worsening of an accident by quickly and easily removing the coverall thanks to the red anti-panic zip.
- Adjustable to all body types: elastic waist, adjustable length of inner leg (77 cm or 82 cm).



**Features:**

- A high collar and adjustable cuffs improve the coverall's high protection.
- Hard-wearing coverall thanks to the reinforcements at the knees, crotch and bottom of the zipper.
- Numerous features: 1 chest band, 2 chest pockets, 2 Italian pockets, 2 cargo pockets.
- Standard pictograms clearly visible on the left sleeve.

Reference	Composition	Size	ATPV (cal/cm <sup>2</sup> )	Box Test	Couleur
AFG-1001-XS	Combinaison	XS	12	APC 1	■
AFG-1001-S	Combinaison	S	12	APC 1	■
AFG-1001-M	Combinaison	M	12	APC 1	■
AFG-1001-L	Combinaison	L	12	APC 1	■
AFG-1001-XL	Combinaison	XL	12	APC 1	■
AFG-1001-2XL	Combinaison	2XL	12	APC 1	■
AFG-1001-3XL	Combinaison	3XL	12	APC 1	■
AFG-1001-4XL	Combinaison	4XL	12	APC 1	■
AFG-1001-5XL	Combinaison	5XL	12	APC 1	■