

## MS-918-..

Network Type : LV

### Low Voltage detector DETEX

#### Application:

- Check the presence of voltage.
- Checks voltage levels from 12 to 900 V AC, 12 to 1 000 V DC.
- Sound and light continuity for a non-live circuit (threshold of 80 Ω).
- Search for the polarities of a DC circuit.
- Unipolar phase identification.
- Phase rotation detection check (two-wire method).
- For indoor / outdoor use.



#### Features:

- Fitted with IP2X test lead points with retractable trigger tips.
- Total safety with hazardous voltage indicator light (> 50 V).
- Protection level: IP65/IK06.
- Self test button to discern the verification of the good functioning and the continuity function.
- Completely modular and adjustable to eclipse sockets.
- Equipped with a lighting lamp at the measuring point.
- LED display.

#### Composition:

- Supplied with soft carrying case and belt loop Ref. [M-87285](#).

#### Optional accessories:

- 2 test plug adapters to be fixed on IP2X test lead points with retractable trigger tips enabling to target test plugs Ø 4 mm. Ref. [DX-04](#)
- Holder, Ref. M-952325.
- Contact probes for L.V. detectors for installation and sidewalk boxes. Ref. [M-8013](#).
- Contact probes for L.V. detectors for flight path. Ref. [M-8014](#).
- Hand stick & stick extension. Ref. [M-951143](#).

Référence	Dimensions	Frequency	Weight (kg)
	Length (mm)		
MS-918-PG	165	50/60/400 Hz	0,21