

KIT-VE...


Kit for application in the field of electric and hybrid vehicles and machines for live working

Application :

- Suitable for electric and hybrid vehicles and machines operations.
- Suitable for work in the vicinity or under voltage (maximum operating voltage 1000 V AC – 1500 V).

Composition:

- 1 insulating flexible mat used to insulate bare or insufficiently insulated conductive parts during interventions. IEC 61112 Class 0; dimensions: 1 x 1 m [MP-220](#).
- 3 clamps for fastening elastomer or plastic insulating or protective mats. Suitable for working under tension or in the vicinity of structures under tension. Length: 80 mm [MP-627-D](#).
- Insulating caps are used to insulate the stripped end of an insulated conductor. They must be pushed onto the insulation of the stripped cable with an overlap :
 - 4 x Insulating caps dimensions: 15 x 100 mm. [MP-635/15-D](#)
 - 4 x Insulating caps dimensions: 30 x 120 mm [MP-635/30-D](#)
 - 2 x Insulating caps dimensions: 60 x 140 mm [MP-635/60-D](#).
- 1 red insulating adhesive tape for masking, fixing, colour coding or packaging operations. Dimensions: 50 m x 50 mm [MP-19/1](#).
- 1 insulating cover for bare parts or parts that are undervoltage to provide protection in case of inadvertent contact. Dimensions: 305 x 225 mm. [MP-29/3-S](#).
- 20 self-adhesive warning sign "LOCAL BATTERY". Side of 10 cm. [AT-67/1](#).
- 1 CAT III 600 V multimeter with LCD digital display for measuring AC and DC voltages, AC and DC currents as well as resistances, capacitances and temperature. [MX-701](#).
- 1 rescue stick 45 kV 1.65 m with insulated hook [CS-45/2](#).
- 1 socket set 3/8" with ratchet and extension (140 mm) in case. Female hex sockets: 8-10-12-13-14-17-19-21-22-23; male hex sockets: 3-4-5-6-8; Torx sockets: TX15-TX20-TX30-TX40-TX50. [MO69308/HAT-D](#).
- 1 insulated brush [MO-710-D](#).
- 1 insulated mirror [MO-755-D](#).
- 1 insulated screwdriver set for live working. Flat-blade screwdriver: 4-6-8 mm; Pozidriv screwdriver: PZ1, PZ2. IEC 60900. [KIT-23](#).
- 1 pliers with angled jaws 160 mm. IEC 60900. [MO-72142](#).
- 1 magnet insulated gripping tool mounted on flexible shaft. [MO-7582-D](#).
- 1 insulated cable cutter 170 mm. IEC 60900. [MO-67501](#).
- 1 3/8" insulated reversible torque wrench. Torque: 4 to 20 N.m. IEC 60900. [MO-69051](#).



Ref

KIT-VEH-V-TST