

## PP-4-38-...

Insulating safety padlock with retaining key, nylon shackle H 38 mm Ø 4 mm

### Application :

- For locking the separating devices (e.g. circuit breakers) to prevent their operation.
- Lightweight padlock with shock-resistant polyamide body: easy to carry.
- Padlock with insulating shackle for use in low voltage 1000 V AC - 1500 V DC: tested and validated in accordance with the electrical test IEC 60900 (2012) §5.5.3. at 5 000 V.
- More secure locking: impossible to drop the key when the shackle is open, the key remains trapped.

### Features :

- Available with a keys alike (A1 to A8) or different (Z).
- Marking on both sides:
  1. On one side: Standard symbol.
  2. On the other side: area for marking user names and coordinates.
- Padlock delivered with 2 keys.



Ref.	Description		Diameter	Characteristics	
	Color	Key Number	Shackle	Weight	
PP-4-38-B-..	■	A1 -> A6 & Z	4	90g	
PP-4-38-Y-..	■	A1 -> A6 & Z	4	90g	
PP-4-38-G-..	■	A1 -> A6 & Z	4	90g	
PP-4-38-W-..	□	A1 -> A6 & Z	4	90g	
PP-4-38-BK-..	■	A1 -> A6 & Z	4	90g	
PP-4-38-O-A7	■	A7	4	90g	
PP-4-38-P-A8	■	A8	4	90g	